


DAYO VALVES CORP.-JAPAN

Cast Iron Butterfly Valve (Lock Lever)

ANSI 150



SPECIFICATIONS

Part	Material
Body	Cast Iron A126 CL.B
Disc	Stainless Steel T304/316 Ductile Iron FCD 45
Disc seat ring	EPDM: 0 TO 90°C NBR: 0 TO 70°C
Stem	SUS 304
Pin	SUS 304
Handle	Ductile Iron FCD 45
Indicate Gear	SS 41

300psi Water, Oil, Gas 65°C
 150psi Saturated Steam
 Designed as standard: BS5155, DIN3202, ISO5752
 Top mounting flange as standard: ISO5211

Primary Service Pressure Non-Shock (psi)	Hydrostatic Test Pressure	
	Shell	Seat
150	300	220


Dimension

Unit : mm

	2	2-1/2	3	4	5	6	8	10	12
Size	50	65	80	100	125	150	200	250	300
L	43	46	46	52	56	56	60	68	78
H	160	179	181	201	216	242	256	300	325
D	102	102	133	146	183	217	260	330	375

Cast Iron Butterfly Valve GEAR OPERATED

ANSI 150



SPECIFICATIONS

Part	Material
Body	Cast Iron A126 CL.B
Disc	Stainless Steel T304/316 Ductile Iron FCD 45
Disc seat ring	EPDM: 0 TO 90°C NBR: 0 TO 70°C
Stem	SUS 304
Pin	SUS 304
Handle	Ductile Iron FCD 45
Indicate Gear	SS 41

300psi Water, Oil, Gas 65°C
 150psi Saturated Steam
 Designed as standard: BS5155, DIN3202, ISO5752
 Top mounting flange as standard: ISO5211

Primary Service Pressure Non-Shock (psi)	Hydrostatic Test Pressure	
	Shell	Seat
150	300	220

Dimension

Unit : mm

	2	2-1/2	3	4	5	6	8	10	12
Size	50	65	80	100	125	150	200	250	300
L	43	46	46	52	56	56	60	68	78
H	160	179	181	201	216	242	256	300	325
D	102	102	133	146	183	217	260	330	375